

SOLIS

SOLIS-5K-2G



LEADING FEATURES.

- Over 97.8% Max. Efficiency
- Ultra wide input voltage range
- Dual MPPT design with precise MPPT algorithm
- Compact and light design for one-person easy installation
- IP65, visually pleasing for domestic environment
- RS 485, WiFi/GPRS (optional) interface
- Numerous protection functions
- WiFi monitoring app available
- 5 years standard warranty, 10 years optional upgrade

MODEL	SOLIS-5K-2G
Input Side (DC)	
Max. input power	5.8kW
Max. input voltage	600V
Start-up input voltage	120V
MPPT voltage range	100-500V
Max. input current	15A+15A
MPPT number/Max. input strings number	2/2

MODEL SOLIS-5K-2G	
Output Side (AC)	
Rated output power	5kW
Max. Transient power	5kW
Rated grid voltage	220/230/240V
Grid voltage range	180-270V (adjustable)
Rated grid frequency	50/60Hz
Operating phase	Single
Max. output current	23.8A
Power factor	>0.99
Total harmonic distortion (THDi)	<3%
DC injection current	<20mA
Grid frequency range	47-52Hz or 57-62Hz(adjustable)

Protection	
DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Output over voltage protection	Yes
Insulation resistance monitoring	Yes
Residual current detection	Yes
Surge protection	Yes
Grid monitoring	Yes
Islanding protection	Yes
Temperature protection	Yes
Integrated DC switch	Optional

MODEL SOLIS-5K-2G	
Efficiency	
Max. efficiency	97.8%
EU efficiency	97%
MPPT efficiency	99.9%

General data	
Dimensions	339W*565H*172.5D(mm)
Weight	16.5kg
Topology	Transformerless
Self consumption	<1W(Night)
Operating ambient temperature range	-25°C-60°C
Ingress protection	IP65
Noise emission (typical)	<30 dBA
Cooling concept	Natural convection
Max. operation altitude	2000m
Designed lifetime	>20 years
Grid connection standard	UL1741, G83/2, AS4777,VDE0126-1-1
Relative humidity	0-95%
Safety/EMC standard	EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100

Features	
DC connection	MC-4 mateable
AC connection	IP67 rated plug
Display	LCD, 2X20 Z
Interface	RS 485, WiFi/GPRS (optional)
Warranty	5-10 Years